



U2TM mobile

It's ultra portable, lightweight and easy-to-operate. Introducing the world's most compact mobile printer, the U2-mobile.



Ultra Lightweight
The world's lightest mobile printer, weighing only 1kg (2.21Lb)



Full-Color Large LCD Display
2.8-inch color LCD with LED backlit screen



All in ONE BOX
One tiny box with all the accessories you will ever need: U2 mobile, remote keypad, 2 high capacity rechargeable batteries, battery charger, SD card & SD card reader



SD Card Slot Design
Easy software upgrade and data backup



Ultra Portable
Capable of printing anywhere, at any angle, without ink leakage



Plug-n-Print
Ink cartridge design with no maintenance and downtime costs



Long Lasting Battery
7 hours of continuous printing with more than 200,000 characters



600 dpi (For U2 HD Only)
2X the resolution for printing crisp & precise HD barcodes. Now available on both U2 & U2-mobile.



Remote Keypad
Pocket-size remote keypad with user-friendly operation



More Ink Selections
Now you can print onto a variety of substrates using ANSER's new Infinity ink family

U2TM mobile



Print at anywhere at any angle !

- Ultra Portable
- Ultra Lightweight
- Long Lasting Battery



U2-Mobile Specifications

Display
LED Indicators
Available Languages

Operation Menu
Input Device
Plug-n-Print Design
Printable Images

Printable Lines & Heights

Print Speed
Message Storage Capacity
Dimension (L/W/H)
Weight

Long Lasting Battery

Rated Capacity
Standard Voltage
Input/Output Voltage
Charging Voltage
Charging Hours
Charging Temperature Range
Discharging Temperature Range
Dimension (L/W/H)
Weight
Cycle Life
Continuous Printing Hours
Stand-by Time

Ink Solutions

Environment

Operating Temperature Range

2.8" full-color LCD with LED backlit
5 indicators: Alarm, Ink low, Print, Run, Remote on/off
English, Japanese, French, German, Spanish, Portuguese, Russian, Korean, Italian, Turkish, Chinese (Traditional & Simplified)
Digital Menu Selection (DMS) for easy operation
Pocket-size IR remote keypad
Hewlett-Packard TIJ 2.5 printing technology
Alphanumeric, logo, date/time, expiry date
shift code, counter, lot-box code and barcode
1, 2, 3, 4 lines. Total line height is limited to 12.7mm (0.5")
Heights: 2.7mm, 3.6mm, 5.5mm, 8mm, 10mm, 12.7mm (0.11", 0.14", 0.22", 0.31", 0.39", 0.5")
57 meters (148 feet) / minute at 400 dpi horizontal resolution
Store up to 999 messages with SD card
212 x 135 x 120 (mm) / 8.3 x 5.3 x 4.7 (inch)
1Kg (2.20Lb) – exclude cartridge and battery

3,700 mAh
11.1V
12.6V
12.6V
2.5 hours
0°C – 45°C (32°F – 113°F)
-10°C – 45°C (14°F – 113°F)
65 x 51 x 37 (mm) / 2.5 x 2 x 1.5 (inch)
165g (0.36Lb)
More than 300 cycles
7 hours
9 hours

A wide range of ink selections for printing on porous, semi-porous and non-porous substrates

5°C – 40°C (41°F – 104°F)